

SPECIAL PRODUCTS **ADCON CLEANER FW**

Environmentally friendly, superior-quality special cleaner for all types of concrete formwork based on renewable raw materials with corrosion inhibitor

APPLICATION:

- » Circulation systems
- » Precast plants
- » In-situ concrete construction sites
- » Long-term storage of formwork

ADVANTAGES:

- » Special cleaner for all types of formwork
- » Corrosion protection
- » Low viscosity
- » Low consumption and easy processing

PRODUCT DESCRIPTION


3CS® AdCon CLEANER FW is a low-viscosity special cleaner for all formwork in concrete construction based on renewable raw materials. **3CS® AdCon CLEANER FW** has a strong cleaning power and effortlessly removes dust, oil, grease and adhesive residues from the formwork. The remaining film protects against rust and also provides even better separation from the formwork. An additional cleaning effect can be achieved with a floor sander and felt disk.

ADVANTAGES

With **3CS® AdCon CLEANER FW**, all types of formwork can be effectively cleaned, protected against new soiling and kept clean in the long term. Steel formwork is sustainably protected by a special corrosion inhibitor. **3CS® AdCon CLEANER FW** is user-friendly and easy to apply without leaving a sticky residue on the formwork like other cleaners.

PROCESSING

Apply **3CS® AdCon CLEANER FW** undiluted to the formwork to be cleaned with a fine spray mist using a high-pressure sprayer or automatic release agent dispenser. When spraying, ensure sufficient spray pressure (at least 4 bar). The surface can then be cleaned with a floor sander and felt disc. The surface should also be scraped with a rubber scraper. Slight differences in the color of the cleaner are possible due to the batch production, but have no influence on the product performance or on the concrete surface.



STORAGE CONDITIONS

Storable for at least 12 months in the original sealed container at temperatures from +5 °C to +30 °C. Store in a dry place and protect from direct sunlight, frost and contamination. Do not mix concrete release agents with other concrete release agents or substances.

SAFETY INSTRUCTIONS

Please observe the hazard warnings and safety advice on the labels and in the safety data sheets.

TECHNICAL SPECIFICATIONS

DENSITY	0.84 g/cm ³
STATE	liquid
COLOR	yellowish, translucent
ODOUR	Characteristic
WATER HAZARD CLASS (WGK)	1 (slightly hazardous to water)

ARTICLE NUMBER	UNIT	PACKAGING UNIT
B501022364801	lt	1000 lt IBC
B501022364811	lt	200 lt drum
B501022364832	lt	25 lt can

This data sheet, like our other technical information, serves only to describe the nature of this product and the processing and application options. However, it is not intended to guarantee certain product properties or fitness for a specific purpose, and the description does not contain complete instructions for use. As we reserve the right to make changes to our data sheets, it is the customer's responsibility to ensure the availability of the up-to-date data sheet. Current information sheets can be requested at any time from any of our premises. Typos, technical changes and errors excepted. In addition, our general terms and conditions apply. **Version: 09/03/2026**

