

# RELEASE AGENT **EASYMOLD TR-L 123**

Superior quality special release agent for the concrete industry in precast plants and on construction sites, approved for drinking water tank construction

## APPLICATION:

- » Drinking water tank construction
- » Precast plants
- » In-situ concrete construction sites

## ADVANTAGES:

- » Suitable for exposed concrete
- » Rapidly biodegradable
- » Corrosion protection
- » Low viscosity
- » Low consumption and easy processing

## PRODUCT DESCRIPTION

**3CS® EasyMold TR-L 123** has good adhesion and very good release properties. When used properly, **3CS® EasyMold TR-L 123** does not build up, or form pores. Approved for drinking water tank construction. When used properly, **3CS® EasyMold TR-L 123** produces concrete surfaces of the highest quality. At the same time, the formwork is kept clean.

## ADVANTAGES

Due to its low viscosity, the product can be applied economically. **3CS® EasyMold TR-L 123** can be used to produce visually appealing concrete surfaces. Steel formwork is sustainably protected by a corrosion inhibitor. **3CS® EasyMold TR-L 123** is suitable for application on vertical and horizontal surfaces and is very easy to wipe off.

## PROCESSING

Apply **3CS® EasyMold TR-L 123** undiluted to the cleaned formwork with a fine spray mist using a high-pressure sprayer or automatic release agent dispenser. When spraying, ensure sufficient spray pressure (at least 4 bar). Remove puddles and excess using a cleaning cloth or squeegee with a rubber lip.

Economical consumption and easy handling during application are decisive parameters for a shrinkage-free and low-porosity concrete surface after stripping. If applied correctly, no negative influence on the adhesion of subsequent coatings (plasters, paints, etc.) is to be expected. Slight color differences are possible due to the batch production, but have no influence on the product performance or on the concrete surface.



## STORAGE CONDITIONS

Storable for at least 12 months in the original sealed container at temperatures from +5 °C to +30 °C. Store in a dry place and protect from direct sunlight, frost and contamination. Do not mix concrete release agents with other concrete release agents or substances.

## SAFETY INSTRUCTIONS

Please observe the hazard warnings and safety advice on the labels and in the safety data sheets.

## TECHNICAL SPECIFICATIONS

|                                 |  |                                     |
|---------------------------------|--|-------------------------------------|
| <b>COLOR</b>                    |  | yellowish, translucent              |
| <b>STATE</b>                    |  | liquid                              |
| <b>DENSITY</b>                  |  | approx. 0.830 g/cm <sup>3</sup>     |
| <b>ODOUR</b>                    |  | characteristic                      |
| <b>AVERAGE CONSUMPTION</b>      | depending on application and formwork type | 1 liter for 70 - 100 m <sup>2</sup> |
| <b>WATER HAZARD CLASS (WGK)</b> |  | 1 (slightly hazardous to water)     |
| <b>GISCODE</b>                  |  | BTM 20                              |

| <b>ARTICLE NUMBER</b> | <b>UNIT</b> | <b>PACKAGING UNIT</b> |
|-----------------------|-------------|-----------------------|
| <b>B102021181201</b>  | lt          | 1,000 lt IBC          |
| <b>B102021181211</b>  | lt          | 200 lt drum           |
| <b>B102021181232</b>  | lt          | 25 lt can             |
| <b>B102021181235</b>  | lt          | 5 lt can              |

This data sheet, like our other technical information, serves only to describe the nature of this product and the processing and application options. However, it is not intended to guarantee certain product properties or fitness for a specific purpose, and the description does not contain complete instructions for use. As we reserve the right to make changes to our data sheets, it is the customer's responsibility to ensure the availability of the up-to-date data sheet. Current information sheets can be requested at any time from any of our premises. Typos, technical changes and errors excepted. In addition, our general terms and conditions apply. **Version: 13/03/2026**

